


UV-Integrator 04

The UV-Integrator 04 is a high quality UV measuring instrument. It is used to measure UV energy of different light sources, especially on printing machines. It is ideal to ensure quality control of printing and drying processes.

With its round shape and a diameter of only 4.7" (120 mm/CD size) it bears a small risk to get stuck somewhere inside. It is reliable and simple to use.

The UV-Integrator 04 is available in six different measuring ranges*:
(Please state upon order)

Item 1.1 UV-Integrator 04, Type 1 Diazo	350 – 460 nm
Item 1.2 UV-Integrator 04, Type 2 UV-A	315 – 410 nm
Item 1.3 UV-Integrator 04, Type 3 UV	250 – 410 nm
Item 1.4 UV-Integrator 04, Type 4 UV-B	280 – 315 nm
Item 1.5 UV-Integrator 04, Type 5 UV-C	230 – 280 nm
Item 1.6 UV-Integrator 04, Type 1 UV-V	395 – 445 nm




By addition of the incidence of the light quantities during the exposure cycle, relative values are calculated.

Because of uneven radiation distribution of the UV light source and different type of construction of the measuring devices by different manufacturers, different readings may appear under the same measurement conditions.

Technical Data:

Spectral range:	UV 250 – 410 nm
Measuring range:	0 to 5,000 mW/cm ²
Display:	6-digit LCD
Display range:	0 to 999,999 mJ/cm ²
Power source:	long life 3.6 V Lithium Battery
Power consumption:	100 µA
Battery service life:	10,000 hrs
Dimensions:	Ø 4.7" (120 mm), height ½" (13 mm)
Weight:	approx. 9 ounce (260 grs.)
Temperature range:	0 to 45° C / 32 to 113° F
Heat protection:	Heat shield on back plate
Base Accuracy:	± 5 %

In the standard version it is measuring an integral in the spectral range from 250-410 nm, with a peak at the area of 330 nm.



While on the conveyer belt, the UV-Integrator 04 can withstand max. 110° C / 230° F for up to 10 seconds. The temperature of the housing should not exceed 45° C / 113° F.

Calibration:

In order to keep its full function and precision it is recommended to have re-calibration done once per year. Ongoing, PTB traceable calibration with certificate.

*further spectral ranges available upon request

Subject to change without prior notice © 2014-02

UV-DESIGN (Office)
Triebstrasse 3
63636 Brachtal
GERMANY
Tel.: +49 (0)6053 619824
Fax: +49 (0)6053 619820

(Office & Workshop) UV-DESIGN
Fabrikstrasse 12
63636 Brachtal
GERMANY
Tel.: +49 (0)6053 8095431
Fax: +49 (0)6053 8095433